



	QX900 F	QX900 C	QX900 S
<b>POWER HANDLING</b>	300 Watt	150 Watt	150 Watt
<b>FREQUENCY</b>	38Hz - 22Khz	65Hz - 22Khz	65Hz-22Khz
<b>SENSITIVITY (+/- 3DB)</b>	89db	89db	89db
<b>NOMINAL IMPEDANCE</b>	4 - 8 Ohm	4 - 8 Ohm	4 - 8 Ohm
<b>DRIVER COMPLEMENT</b>	3 way Drav Fig.	2 way DRAV FIG. magnetic shielding bass reflex	2 way DRAV FIG.
<b>WOOFER</b>	Two 6.5" (165-mm) woofer FPC CON for low frequencies	Two 5.25" (133-mm) midwoofer- driver FPC CON	One 5.25" (133-mm) midwoofer- driver FPC CON
<b>MIDRANGE</b>	One 6.5" (165-mm) Mid-Driver FPC CON for mid frequencies		
<b>TWEETER</b>	1" (25-mm) silk SCOS dome	1" (25-mm) silk SCOS dome	1" (25-mm) silk SCOS dome
<b>CROSSOVER FREQUENCY</b>	2500 / 3500 Hz	2700 Hz	3500 Hz
<b>DIMENSIONS (HXWXD)</b>	111x21x32 Cm	17.5x55x18.5 Cm	34x17.5x18.5 Cm
<b>WEIGHT</b>	17 Kg (38 Lbs) each	5 Kg (11 Lbs)	3 Kg (7 Lbs) each
<b>FINISH</b>	Black, Silver, Cherry, Beech, Mahogany, Maple	Black, Silver, Cherry, Beech, Mahogany, Maple	Black, Silver, Cherry, Beech, Mahogany, Maple
<b>GRILLE</b>	Black cloth	Black cloth	Black cloth

*Design and specifications are subject to change without notice.*

[www.pure-acoustics.com](http://www.pure-acoustics.com)